

AL JAZEERAH MARINE

info@aljazeerahmarine.com sales@aljazeerahmarine.com

ADDRESS: EMIRATES INDUSTRIAL CITY SAJAA SHARJAH UAE



+971-54-7070379

www.aljazeerahmarine.com

Swivel Forerunner

1. Swivel Forerunner (Swivel Piece)-Anchor Chain accessories Swivel Forerunner (Swivel Piece) include End Link, Enlarged Link, Swivel, Enlarged Link and Common Link, commonly used to connecting End Shackle and anchor chains.

Joining the stud link chain and the anchor, a 3-link or 4-link swivel forerunner is the most common swivel-connector in use today due to its optimal design. The anchor-side of the swivel forerunner is open for fitting a "D" end shackle. The other side is a common link to fit a Kenter joining shackle. The swivel forerunner is produced to ISO 1704 standards.

2. Specification for Swivel Forerunner Regular Joining Form: E+EL+SW+EL+C

Material: Steel CM490/CM690

Grade: U2/U3

Nominal Diameter: 12.5mm to 162mm



Product Details:

Type: 5-link adaptor = E+EL+SW+EL+C

Grade: Grade 2 & 3

Material: alloy steel/carbon steel/stainless steel

Chain Dia	Length MM	Chain Dia	Length MM	Chain	Length MM
12.5	251	30	602	50 52 54 56 58	1003
14 16 17,5	Mr. of 281	32	642	01152	1043
16 0	321	34	682	⁵⁴	1083
17.5	351	36	722	56	1123
·/ 19	381	38	. 62	58	1163
20.5	411	40	802	60	1203
22	441	42	842	62	1243
24	481	44	882	64	1283
26	521	46	922	66	1323
28	561	48	962.0	68	1363
70	1404	97	2005	124	2486
73	1464	100	2005	127	2546
76	1524	102	2045	130	2607
78	1564	105	2105	132	2647
81	1624	107	2145	137	2747
84	1684	111	2226	142	2847
87	1744	114	2286	147	2947
90	1805	117	2346	152	3048
92	1845	120	2406	157	3148
95	1905	122	2446	162	3248